UC Hastings Window Replacement 100 McAllister St., San Francisco, CA

ABBREVIATIONS

F.D.

FDN.

FINISH

AND AT ANCHOR-BOLT A.B. A/C AIR-CONDITIONING ACOUStICAL ACOUS AREA DRAIN A.D. ADJ. ADJUSTABLE AGGR AGGREGATE ALUMINUM AL ALT. ALTERNATE ANOD. ANODIZED APPROX APPROXIMATE ARCH. ARCHITECTURA ASPH. ASPHALT B.D. BOARD BITUM BITUMINOUS B.F. BASE FLASHING BLDG BUILDING BLK. BLOCK BI KG BI OCKING BLW. BELOW BM. BEAM BOT. BOTTOM BSMT BASEMENT BTWN. BETWEEN BUILT-UP ROOFING B.U.R C.B. CATCH BASIN CEM. CEMENT COUNTERFLASHING CFL. CAST IRON C.I. C.I.P CAST-IN-PLACE C.J. CONTROL JOINT CLG. CEILING CLKG. CAULKING CLR. CLEAR CMU. CONCRETE MASONRY UNIT CNTR COUNTER COL. COLUMN COMF COMPOSITION CONC CONCRETE CONT. CONTINUOUS CORR. CORRIDOR CTR. CENTER CTSK COUNTERSUNK C/W COMPLETE WITH DBL. DOUBLE DEPT DEPARTMENT D.D. DECK DRAIN D.F. DOUGLAS FUR D.F.T. DRY FILM THICKNESS DIAMETER DIA. DIAG DIAGONAL DIM. DIMENSION DOWN DN D.P. DAMPPROOFING DOOR DR DOWNSPOUT DS D.S.P. DRY STANDPIPE DTL. DETAIL DWG. DRAWING EAST EXISTING (E) E.A EACH E.B. EXPANSION BOLT EXPANSION JOINT E.J. ELASTOMERIC ELAS ELEV. ELEVATION EXCL ENCLOSURE E.Q. EQUAL EQPT EQUIPMENT EXP. EXPANSION EXPO. EXPOSED EXT. EXTERIOR

FIN. FLOOR FL. FLASH. FLASHING FACE OF CONCRETE F.O.C. F.O.F. FACE OF FINISH F.O.S FACE OF STUDS F.S. FULL SIZE FT. FOOT OR FEET FTG. FOOTING FURR. FURRING G.A. GAUGE GALVANIZED GALV. G.L. GLASS GND. GROUND GRADE GR. GSM. GALVANIZED SHEET METAI GYP GYPSUM H.B. HOSE BIBE H.C HOLLOW CORI HDG. HOT DIPPED GALVANIZED HGT. HEIGHT H.M. HOLLOW METAL HORIZ. HORIZONTAL H.P. HIGH POINT HR. HOUR H.W. HOT WATER I.D. INSIDE DIAMETER INT. INTERIOR INV. INVERT JT. JOINT ANGLE LAG BOLT L.B. L.P. LOW POINT LT. LIGHT LVR. LOUVER L.W. LIGHTWEIGHT MAX. MAXIMUM M.B. MODIFIED BITUMEN MECH. MECHANICAL MEMB. MEMBRANE MET. METAL MFR. MANUFACTURER MIN. MINIMUM MISC. MISCELLANEOUS MTD. MOUNTED MTL. MATERIAL MUL. MULLION NORTH N. NEW (N) N.I.C. NOT IN CONTRACT NO OR # NUMBER NOM. NOMINAL N.T.S. NOT TO SCALE O/ OVER OVERALL O.A. 0.C. ON CENTER OUTSIDE DIAMETER O.D. O.F. OVERFLOW O.F.D. OVERFLOW DRAIN OPNG. OPENING OPP. OPPOSITE P.C. PHOTO CELI P.E.N. PERIMETER EDGE NAILING P.L. PLATE PLAS. PLASTER PLYWD. PLYWOOD PT. POINT

FLOOR DRAIN PT FOUNDATION SQ. S.S. STA. T.C. TEL. T. & G. THK. T.P. T.S. T.W. TYP. UNF. U.O.N. VERT. VEST. V.I.F. V.S. W. W/ WD. WIN. W/O W.O. WP. WT. W.W.F.

P.T.D.F PRESSURE TREATED DOUGLAS FIR R/R **REMOVE & REINSTALL** REMOVE (R) RISER R & S **ROD & SEALANT** RAD. RADIUS R.D. ROOF DRAIN REF. REFERENCE REINE REINFORCED R.S.P. REINFORCED STEEL PIPE REQ. REQUIRED RESIL. RESILIENT RM. ROOM R.O. ROUGH OPENING R.W.L. RAIN WATER LEADER SOUTI SAM SELF ADHERED MEMBRANE S.C. SOLID CORE SCHED. SCHEDULE SECT. SECTION S.G.D. SLIDING GLASS DOOR SH. SHELF SHT. SHTG. SIM.


PRESSURE TREATER

SHEET SHEATHING SIMILAR SQUARE STAINLESS STEEL S.S.D. SEE STRUCTURAL DRAWINGS STATION STD. STANDARD STL. STEEL STOR. STORAGE STRL. STRUCTURAL SYM. SYMMETRICAL TOP OF CURB

TELEPHONE **TONGUE & GROOVE** THICK THRESH. THRESHOLD TOP OF PAVEMENT TUBE STEEL TOP OF WALL TYPICAL UNFINISHED UNLESS OTHERWISE

NOTED VERTICAL VESTIBULE **VERIFY IN FIELD** VENT STACK WEST WITH WOOD WINDOW WITHOUT WHERE OCCURS WATERPROOP WEIGHT WELDED WIRE FABRIC

LEGENDS AND SYMBOLS



PROJECT GENERAL NOTES

ALL WORK SHALL CONFORM TO THE CURRENT ADOPTED VERSION OF THE UBC AND ANY LOCALLY ADOPTED CODES OR ORDINANCES BY THE CITY OF SAN FRANCISCO OR UBC.

THE INTENT OF THE DOCUMENTS IS TO INCLUDE ALL ITEMS NECESSARY FOR THE PROPER EXECUTION AND COMPLETION OF THE WORK. THE DOCUMENTS ARE COMPLEMENTARY AND WHAT IS REQUIRED BY ANY ONE SHALL BE AS BINDING AS REQUIRED BY ALL. IN CASE OF CONFLICT, THE MORE RESTRICTIVE REQUIREMENT SHALL GOVERN.

CONTRACTOR SHALL VERIFY EXISTING (E) CONDITIONS AND THOSE SHOWN ON THE DRAWINGS. CONTRACTOR SHALL NOTIFY ARCHITECT IF CONDITIONS VARY FROM THOSE SHOWN OR IF HIDDEN CONDITIONS EXIST WHICH WOULD BE DETRIMENTAL TO PROPER INSTALLATION.

DRAWINGS ARE BASED ON ORIGINAL DESIGN SET AND DO NOT NECESSARILY REFLECT AS-BUILT CONDITIONS. THE CONTRACTOR SHALL VERIFY ALL EXISTING FIELD CONDITIONS, DIMENSIONS, AND QUANTITIES. EXACT QUANTITIES, TYPES, LOCATIONS, AND MEASUREMENTS ARE THE RESPONSIBILITY OF THE CONTRACTOR, INCLUDING, BUT NOT LIMITED TO ALL WINDOWS AND DOORS DESIGNATED FOR REPLACEMENT.

DURING THE WORK, THE CONTRACTOR SHALL PROVIDE ALL NECESSARY MEANS FOR ACCESS TO THE WORK (I.E. SWINGSTAGES, MAN LIFTS, AND/OR SCAFFOLDING, ETC.)

CONTRACTOR WILL BE RESPONSIBLE FOR ALL PERMITS

PROTECTION OF ALL HARDSCAPE (SIDEWALKS, DRIVEWAYS, ETC.) AND SOFTSCAPE (LANDSCAPE, IRRIGATION LINES, ETC.) IS REQUIRED DURING THE WORK.

CONTRACTOR SHALL PROVIDE BARRICADES AND TEMPORARY DEBRIS BARRIERS WHETHER SHOWN ON DRAWINGS OR NOT, AS NECESSARY TO PROTECT TENANTS AND OWNER'S EQUIPMENT, FURNISHINGS, OPERATIONS AND AREAS FROM DAMAGE UNWARRANTED INTERRUPTION, UNAUTHORIZED ENTRY, CONSTRUCTION HAZARDS OR UNNECESSARY INCONVENIENCE DURING ALL OPERATIONS UNDER THIS CONTRACT.

CONTRACTOR SHALL KEEP MEANS OF EGRESS AND DRIVEWAYS CLEAR AT ALL TIMES.

CONTRACTOR SHALL PROVIDE AN ON-SITE TELEPHONE, PORTABLE TOILETS, AND DRINKING WATER.

CONTRACTOR SHALL COMPLY WITH OSHA REGULATIONS.

PROJECT DESCRIPTION

THE PROJECT CONSISTS OF WINDOW REPLACEMENT FOR ENTIRE BUILDING. THE PROJECT SCOPE INCLUDES THE FOLLOWING, NOT LIMITED TO: REMOVAL OF EXISTING WINDOW SASHES AND TRIMS, NEW WINDOW INSTALLATION, REPAIR & REPOINTING OF MORTAR JOINTS, AND SEALANT INSTALLATION AT WINDOW PERIMETER AND COPPER PANELING.

SCOPE OF WORK

- 1. REPLACEMENT OF (E) ENTRY DOORS @ EAST ELEVATION
- 2. INSTALL NEW STAINLESS STEEL PAN FLASHING
- 3. DOOR/WINDOW ASSEMBLEY TO HAVE FIRE-RATED GLASS & PANIC HARDWARE
- 4. INSTALL WEATHERSTRIPPING
- REPOINT BRICKS ALONG DOOR WINDOW JAMBS
- 6. INSTALL NEW SEALANT AT FRAME PERIMETER ON INTERIOR & EXTERIOR

PROJECT DATA/SCAN INFORMATION

SEE THE FOLLOWING FOR ACCESS TO SCAN DATA AND PANORAMIC VIEWS OF PROJECT:

WWW.EPICSCAN.COM CLICK ON TRUVIEW USER NAME: 100 McAllister PASSWORD: hastings

NOTE: ACCESS TO SCAN DATA / TRUVIEW IS ONLY AVAILABLE USING INTERNET EXPLORER BROWSERS

FOR TRUVIEW TRAINING: STEP 1: GOTO EPIC SCAN TRUVIEW PAGE TRUVIEW LINK: HTTP://WWW.EPICSCAN.COM/TRUVIEW LANDING.PHP

STEP 2: INSTALL INTERNET EXPLORER TRUVIEW PLUGIN (V2.1.0.1) HTTP://WWW.EPICSCAN.COM/FILES/TRUVIEWSETUP 2 1 0 1.EXE

STEP 3: LOGIN USER NAME: "PROJECT NAME" PASSWORD: "PASSWORD"

STEP 4: REVIEW TRAINING VIDEO TRAINING VIDEO: HTTP://WWW.YOUTUBE.COM/WATCH?V=HFYY1ZMHWVW

DRAWING INDEX

G-001 TITLE SHEET A-201 ELEVATIONS

A-501 DETAILS A-502 DETAILS

PROJECT INFORMATION

OWNER:

UC HASTINGS, COLLEGE OF LAW SUNNY DHAMRAIT 100 MCALLISTER ST. SAN FRANCISCO, CA 94102 P: (415) 565-4688 F: (415) 565-4884

ARCHITECT:

FERRARI-MOE LLP. 2138 FOURTH ST. SAN RAFAEL, CA. 94901 P: (415) 458-3511 F: (415) 458-3512

- N

- 0 റെ

4 ω

o

ш — 4

- н ч ω ο -

шZ

 $\supset O$

z _ < 4

s _

NO

FORUCTI

NOT


Ο ()


LP

MOE


RRARI









TYPICAL STEEL DOOR 2 SCALE: 1/2" = 1'-0"



EAST ELEVATION SCALE: 1/16" = 1'-0"





	(E) EXTERIOR CLADDING
	TO REMAIN (N) SEALANT JOINT W/
	3/8" MIN. BOND LINE, BACKER ROD, TOOL, TYP.
	(N) STEEL WINDOW ————
	(N) SEALANT BEAD, ——— TOOL, TYP.
	2 TYPICAL STEEL V SCALE: FULL SIZE
	(N) STEEL WINDOW ———
	(N) SEALANT BEAD, ——— TOOL, TYP.
— (N) WINDOW SYSTEM	(N) SEALANT JOINT W/
— (N) SEALANT JOINT @ WINDOW, SEE DETAIL 3/A-501 FOR ADDITIONAL INFORMATION	BACKER ROD, TOOL, TYP.
	(N) SILICONE TAPE, TYP. ———
— AS OCCURS @ STEEL WINDOWS	
— (E) MORTAR JOINT, REPOINT AT ALL JOINTS THAT INTERSECT SEALANT JOINT. CARRY REPOINTING TO ADJACENT MASONRY OPENING CORNER, TYP.	(N) SEALANT @ ——— FASTENER, TYP.
	(N) MOUNTING CLIP PROVIDE CONT. SEALANT
— (N) SEALANT JOINT @ COPPER PANEL, SEE DETAIL 5/A-501	BED, TYP. STEEL TUBE SHIM, SSD. ————
FÓR ADDITIONAL INFORMATION	(N) CUSTOM ALUM. TRIM TO MATCH WINDOW FINISH
	(N) SEALANT JOINT W/
— (E) COPPER PANEL, TYP.	(E) EXTERIOR CLADDING TO REMAIN
	(N) STRUCTURAL ———— ANCHOR, SSD.
	1 TYPICAL STEEL V SCALE: FULL SIZE

